High-performance, Single Drive SCSI Duplication

> The first mixed-master, high-speed, self-contained IDE/SCSI duplication system capable of duplicating an IDE or SCSI master drive to a SCSI target drive at speeds exceeding 2.3 GB/min. This revolutionary system is housed in a slim-line chassis and is self-contained with its own graphic LCD display and control panel.

No Monitor or Keyboard Required

Portable and Self-contained

Transfer Rate Exceeds 2.3 GB/min.

0/S Independent

Brand and Size Unimportant

Supports All SCSI Drives

(50/80 pin Optional)

Embedded Software

MirrorCopy™, CleverCopy™, MasterManager™ and Selective Partitions™






AKL Technology Engineering & Services 23 Woodlands Industrial Park E1 #04-05, Singapore 757741

Tel: +65 68916266, Fax: +65 68916366

Website: www.akl-it.com

Email Address: sales@akl-it.com



Every OmniSCSI Includes:

- OmniSCSI unit
- Power supply
- Software
- Printed operator's manual









S	P	E C		F	1	C	A	T	1	0	N	S
Power Requirements		Power Consumption	Operating Temperature		Relative Humidity	Net Weight		Dimensions		Agency Approvals		
90-230 47/63 Hz		10W without drives	5-60	o° C	10%-80%	n/a		11 W x 16.5 D x 3"H		UI 1950, FCC Part 15 Class A, CE		

AKL Technology Engineering & Services 23 Woodlands Industrial Park E1 #04-05, Singapore 757741

Tel: +65 68916266, Fax: +65 68916366

Website: www.akl-it.com Email Address: sales@akl-it.com

