

## HPX PACKAGED DX ENERGY EFFICIENT UNITS

The HPX range comprises five models, which are fully packaged DX units complete with high efficiency recuperator, compressor pack and controls.

The units are constructed from extruded aluminium framework, which will have a mill finish. Panels will be double skinned as standard constructed from galvanised steel inner skins and pre-painted steel outer skins. The cavity between the skins will be filled with Class I high-density insulation and can be either 25mm or 50mm thick

Units are provided with a G4 synthetic panel with F7 rigid bag filters as an option. Filters will be provided with inclined gauge manometers as standard.

Magnahelic gauge manometers are also available as an option.



Recuperators are of the high efficiency type formed from aluminium plates with a galvanised steel casing. Plates are sealed to prevent cross contamination. The recuperator is utilised during the summer months to provide "free cooling".

## The dynamic heat recovery system utilises R407C within a heat pump refrigeration circuit which will comprise:

- · Scroll compressors.
- Copper/Aluminium evaporator/condenser coils.
- Bifiux thermostatic valves
- 4-way valves for cycle inversion
- High/Low pressure switches
- · Liquid separators and receivers

The control panel will be complete with microprocessor for self-control and self-setting working mode. A remote console is provided for set and display. The unit is supplied with a BMS interface.






## Standard & Special Air Handling Units for Ventilation & Air Conditioning Applications

Model	020	040	060	090	120
Min/Max	0.56 / 0.67	1.11 / 1.33	1.67 / 1.94	2.22 / 2.78	2.78 / 3.89
Max	350	350	350	350	350
Min/Max	0.55 / 1.10	1.10 / 2.20	2.20 / 4.00	2.20 / 5.50	3.00 / 7.50
Max	13.1	26.1	39.2	53.0	69.9
Max	21.9	43.5	65.2	88.5	117.1
	Min/Max Max Min/Max	Min/Max	Min/Max	Min/Max	Model         020         040         060         090           Min/Max         0.56 / 0.67         1.11 / 1.33         1.67 / 1.94         2.22 / 2.78           Max         350         350         350         350           Min/Max         0.55 / 1.10         1.10 / 2.20         2.20 / 4.00         2.20 / 5.50           Max         13.1         26.1         39.2         53.0           Max         21.9         43.5         65.2         88.5

Power Supply: 415V - 3ph - 50Hz



Dimensions	020	040	060	090	120
Height (C) mm					
Depth (B) mm					
Length (A) mm					
5 5					



10 East Park, Crawley, West Sussex, RH10 6AS Telephone 01293 521201 Facsimile 01293 521881

> Email: sales@myventilation.co.uk Web: www.myventilation.co.uk