

Sea Tel 9797

3-Axis marine stabilized antenna system compatible with C-Band, X-Band and Ku-Band satellites

2008 Data Sheet

The most important thing we build is trust

The Model 9797

The Sea Tel Model 9797 radical offset antenna is our most efficient ever C-band, X-band and Ku-Band marine stabilized antenna system. The Model 9797 is both INTELSAT and DSCS compliant. You get more through-put using the same or lesser amount of valuable deck space.


Also available as a dual-band selectable C and Ku-Band system for complete flexibility. Innovative Radical Offset antenna technology provides unparalleled efficiency and performance. An unmatched range of additional powerhouse features means a system you can rely on whatever the weather

or the sea conditions.

The Sea Tel 9707D Utilizes the DAC 2202 Antenna Control Unit. The DAC 2202 is 19" rackmount unit (1.75" tall) featuring: (3) RS-232/422 Serial Ports; (1) full function M&C and (2) NMEA ports for heading, GPS input and modem compatible, reformatted GPS output; (1) Ethernet port allowing (2) full function TCP/IP M&C ports; (1) multi-user HTML interface port for setting all DAC parameters and viewing the current DAC status; (1) UDP download port for updating software in the Comm Interface. DAC 2302 is available for 70/140 MHz receivers.

Specifications

- Receive gain: 46.7dBi @ 6.18GHz 48.45dBi @ 14.25GHz
- Transmit gain: 38.5dBi @ 3.95GHz 47.75dBi @ 11.85GHz
- 20.2 dB/k calculated G/T @ 3.95 GHz (Clear sky, 20 degrees elevation)
- Radome: 3.65m/144" D x 3.6m/142" H
- INTELSAT Earth Station Standard 601 Rev 9
- Sidelobes, 100% below 29-25 log mask
- Compliant to DSCS requirements: X-Band G/T > 22db/k @ 7.5 GHz
- Ship's Motion: +/- 25° Roll or +/- 20° Roll and +/- 15° Pitch
- < 0.2° PEAK mis-pointing @ +/- 25°/15°
- Automatic satellite acquisition
- Circular/linear C/Ku. Circular X-Band
- Automatic linear polang positioning
- Optional KU band drop in feed for dual band operation
- Internal tracking receiver
- Unlimited azimuth (no cable unwrap)
- Built-in test capability, run from antenna control unit or PC
- Windows M&C program/
- All antenna control functions
- M&C for antenna mount RF equipment, up/down converters
- Built-in test includes Strip Chart Recorder
- Remote Diagnostics
- Meets Navy MIL-STD-901D GRADE A shock standards and MIL-STD-461 EMI & RFI standards (including 200V/M)
- Meets MIL-STD-167-1 Vibration



Sea Tel's patented, 3-axis stabilization system isolates the antenna from the ship's motion no matter how rough the weather and seas. The antenna system responds to ship's movement at a rate as fast as 90 degrees per second.

For further information please contact:

Cobham SATCOM Marine Systems

U.S.A. Tel: +1 925-798-7979

U.S.A. Fax: +1 925-288-1420

U.S.A. Toll Free: +1-888-798-7979

U.S.A. E-mail: seatel@cobham.com

EUROPE Tel: +44 2380 671155

EUROPE Fax: +44 2380 671166

EUROPE E-mail: seatel.eurosales@cobham.com